

PVC PACKING TAPE



Color	Width in mm	Length in m	Thickness in mm	Art. No.	P. Qty.
Transparent	50	66	0.055	0985 050	6
brown	50	66	0.055	0985 050 001	6

transparent/brown

- Can be used for all types of packages.
- High resistance to tearing in lengthwise direction.
- Can be unrolled quietly.
- Protects against moisture and damage.
- Slightly structured.
- High adhesive bonding strength.
- Excellent transverse elongation.

Technical Data	
Adhesive basis	Natural rubber
Backing	PVC film (embossed)
Adhesive strength	4.5 N/25 mm
Elongation at tear	70%
Application temperature	+20 °C to +30 °C
Temperature resistance	-20 °C to +80 °C
Shelf life (at approx. +20 °C and 50% humidity)	6 months
UV resistance	Not a given
Moisture-resistance	Not a given

PAPER PACKING TAPE



Width in mm	Length in m	Thickness in mm	Art. No.	P. Qty.
50	50	0.107	0985 050 1	6

brown

- Can be used for light to medium-heavy shipping boxes.
- With reinforced stretching.
- Easy to tear off by hand.
- Solvent-free.
- Environmentally friendly alternative.

Technical Data	
Adhesive basis	Synthetic rubber
Backing	Paper
Adhesive strength	18.8 N/25 mm
Elongation at tear	8%
Application temperature	+10 °C to +25 °C
Temperature resistance	-30 °C to +70 °C
Shelf life (at approx. +20 °C and 50% humidity)	12 months
UV resistance	Not a given
Moisture-resistance	Not a given

PACKING TAPE DISPENSER



with protective cover

- Lowerable blade with protective cover protects against injuries.
- Ergo SoftGrip for user-friendly and pleasant handling.
- Adjustable roller brake for problem-free application.
- Suitable for universal use with all common packing tapes.

Technical Data		
Can be used with	Art. No.	P. Qty.
50 mm tape width	0985 052 005	1